# X2O media

X2O MEDIA PLAYER-S

Full-featured single 4K output media player with remote device management for your visual communications needs.

With an anodized aluminum housing and fanless design it's protected from dust and debris making it an ideal choice for any digital signage solution requiring performance in harsh environments.

SMALL FOOTPRINT, BIG PERFORMANCE

OPTIMIZED ARCHITECTURE FOR DIGITAL SIGNAGE

COMMERCIAL-GRADE RELIABILITY

TECHNICAL SPECIFICATION

X2O | media

Description	Specification
Power	DC input 12V 5A with Screw Lock
Operating System	Windows 10 IoT Enterprise or Linux
Memory	DDR4-3200 SO-DIMM, 2 x 4GB stick, Dual Channel Slots - 32GB Max Total Supported
CPU	AMD Ryzen Embedded R1305G
GPU	AMD Radeon Vega 3
Storage	128GB NVME SSD (M.2 mPCIe 2280), Max 2TB
HDMI	One HDMI 2.0 output
Auxiliary Audio	1 x Auxiliary 3.5 mm Front L/R, 1 x Aux-In/Mic-In
Network	Gigabit Ethernet RJ45 2.4/5 GHz Dual-band WiFi (IEEE 802.11a/b/g/n/ac) Bluetooth v4.0 with BLE Optional: 2nd Ethernet NIC, 4G LTE
Antenna	1 x WiFi/Bluetooth RP-SMA, 1 x 4G SMA
USB	Four USB 3.0 Type A ports
Serial	1 x DB9 Male
Other I/O	Buttons: Power, Reset pinhole WiFi LED, SSD LED, Power button extension RJ11
Dimensions (WxDxH)	With brackets: 281.2 x 180 x 35 mm / 11.07 x 7.09 x 1.38 in Without brackets: 230 x 180 x 33 mm / 9.1 x 7.1 x 1.3 in
Net Weight	2.2 kgs / 4.85 lbs
Enclosure	Anodized aluminum case, fanless
Storage Temperature	-15° - +65° C / +5° - +149° F
Working Temperature	0° - +40° C / +32° - +104° F
Storage/Working Humidity	10 - 90%
Mounting Bracket	Included
Warranty	Warranty* 1 year included, extended warranty available

*Extended 3 or 5 year warranty must be added at time of purchase

Option 1
Cloud-based
CMS

Option 2
On-premise
CMS

S Player

Digital Signage
Screen